

Europower Diesel Generator Sets Powered by Cummins

1500rpm, 50 Hz, 380 - 415V

| Genset | | Prime | | Standby | | Approx. Dimensions, Dry Weight & Fuel Consumption | | | | | |
|---------|-------|-------|-------|---------|--------------|---|--------|--------|--------|------|------|
| Model | kW | kVA | kW | kVA | Engine Model | Alternator Model | L (mm) | W (mm) | H (mm) | kg | I/h |
| EPC25 | 20 | 25 | 21.6 | 27 | 4B3.9-G2 | BCI184F | 1800 | 696 | 1250 | 650 | 8 |
| EPC35 | 28 | 35 | 30.4 | 38 | 4BT3.9-G2 | BCI184H | 1800 | 696 | 1250 | 700 | 9.6 |
| EPC60 | 48 | 60 | 52.8 | 66 | 4BTA3.9-G2 | UCI224D | 1850 | 696 | 1250 | 870 | 12 |
| EPC112 | 89.6 | 112 | 98.4 | 123 | 6BTA5.9-G2 | UCI274D | 2150 | 760 | 1300 | 1135 | 19 |
| EPC125 | 100 | 125 | 109.6 | 137 | 6BTAA5.9-G2 | UCI274E | 2250 | 810 | 1300 | 1140 | 21 |
| EPC150 | 120 | 150 | 133.6 | 167 | 6CTA8.3-G2 | UCI274F | 2350 | 850 | 1350 | 1480 | 30 |
| EPC175 | 140 | 175 | 154 | 192.5 | 6CTA8.3-G2 | UCI274G | 2350 | 850 | 1400 | 1480 | 35 |
| EPC206 | 164.8 | 206 | 181.6 | 227 | 6CTAA8.3-G2 | UCI274H | 2400 | 920 | 1600 | 1500 | 41.7 |
| EPC250 | 200 | 250 | 220 | 275 | 6LTAA8.9G2 | UCD274K | 3150 | 940 | 1740 | 2870 | 50 |
| EPC250 | 200 | 250 | 220 | 275 | NT855-GA | UCD274K | 3150 | 940 | 1740 | 2870 | 50 |
| EPC300 | 240 | 300 | 265 | 330 | NTA855-G1A | HCI444D | 3150 | 940 | 1740 | 2915 | 55 |
| EPC350 | 280 | 350 | 300 | 375 | NTA855-G2A | HCI444E | 3150 | 940 | 1740 | 3080 | 70 |
| EPC375 | 300 | 375 | 329.6 | 412 | NTAA855-G7 | HCI444FS | 3300 | 940 | 1740 | 3194 | 75 |
| EPC405 | 324 | 405 | 356 | 445 | NTAA855-G7A | HCI444F | 3450 | 1100 | 1800 | 4050 | 80 |
| EPC450 | 360 | 450 | 396 | 495 | KTA19-G3 | HCI544C | 3580 | 1250 | 1850 | 4115 | 89 |
| EPC500 | 400 | 500 | 440 | 550 | KTA19-G4 | HCI544D | 3580 | 1250 | 1850 | 4213 | 99 |
| EPC562 | 449.6 | 562 | 495.2 | 619 | KTAA19-G5 | HCI544E | 3720 | 1780 | 2000 | 4605 | 110 |
| EPC587 | 469.6 | 587 | 516.8 | 646 | KTAA19-G6 | HCI544E | 3720 | 1915 | 2288 | 4625 | 116 |
| EPC625 | 500 | 625 | 549.6 | 687 | KTAA19-G7 | HCI544F-S | 3720 | 1915 | 2288 | 4680 | 124 |
| EPC750 | 600 | 750 | 660 | 825 | KTA38-G2 | LVI634B | 4560 | 1650 | 2400 | 7227 | 149 |
| EPC900 | 720 | 900 | 792 | 990 | KTA38-G2A | LVI634D | 4560 | 1850 | 2400 | 8080 | 179 |
| EPC1000 | 800 | 1000 | 880 | 1100 | KTA38-G5 | LVI634E | 4560 | 1930 | 2400 | 8203 | 198 |

Ratings based on ISO3046, BS5514, DIN 6271, $\pm 5\%$ tolerance. Standard reference conditions: air inlet temperature 40° C, altitude 150m asl, fuel weight 0.85kg/l, fuel consumption @75% prime load. Prime rating: Continuous running at variable load. No limit to the annual hours of operations. 10% overload capability for 1 hour in any 12 hours. Standby rating: Emergency power at variable load in the event of utility power failure. No overload is permitted.

* Deration may be necessary at certain voltages.

Due to continually improved products, we reserve the right to make changes in model, technical specs, colour, etc without prior notice.