

## EuroPower Diesel Generator Sets Powered by Mitsubishi. 1500rpm, 50Hz, 380 - 415V

Genset		Prime		Standby		Engine	Approx. Dimensions, Dry Weight & Fuel Consumption			
Model	kW	kVA	kW	kVA	Model	L (mm)	W (mm)	H (mm)	kg	I/h
EPMIT20	16	20	18	22	S4Q2	1480	650	860	400	4.3
EPMIT40	32	40	34	43	S4S-T	1650	720	1100	650	7.0
EPMIT50	40	50	44	55	S4K-T	1800	820	1120	800	10.3
EPMIT70	56	70	62	77	S6K-T	2060	820	1170	1100	12.5
EPMIT85	68	85	75	94	S6K-T	2060	820	1170	1100	15.3
EPMIT118	94	118	100	125	6D16-T	2360	820	1300	1400	22.0
EPMIT200	160	200	-	-	6D22-TC	2780	1090	1400	2150	35.0
EPMIT250	200	250	220	275	S6B-PTA	2780	1180	1560	2500	44.0
EPMIT300	240	300	252	315	S6B-PTA2	2900	1180	1560	2600	50.0
EPMIT375	300	375	330	413	S6B3-PTA	3000	1400	1700	2900	61.0
EPMIT450	360	450	400	500	S6A3-PTA	3000	1480	1900	3700	74.0
EPMIT500	400	500	440	550	S6A3-PTAA	3300	1600	1900	4000	82.0
EPMIT600	480	600	525	656	S6R-PTA	3500	1600	2000	5400	94.0
EPMIT650	520	650	600	750	S6R2-PTA	3800	1600	2000	5500	104.0
EPMIT750	600	750	660	825	S6R2-PTAA	4000	1800	2000	5700	123.0
EPMIT750	600	750	680	850	S12A2-PTA	4000	1800	2000	6500	119.0
EPMIT1000	800	1000	840	1050	S12H-PTA	4300	1800	2450	8100	168.0
EPMIT1275	1020	1275	1120	1400	S12R-PTA	4700	2300	2450	10900	202.0
EPMIT1375	1100	1375	1224	1530	S12R-PTA2	4950	2300	2900	11000	224.0
EPMIT1500	1200	1500	1320	1650	S12R-PTAA2	5100	2300	3050	13000	240.0
EPMIT1735	1388	1735	1520	1900	S16R-PTA	5550	2750	3050	13300	270.0
EPMIT1900	1520	1900	1680	2100	S16R-PTA2	5650	2750	3050	14000	301.0
EPMIT2000	1600	2000	1800	2250	S16R-PTAA2	6000	2750	3500	16000	321.0

Ratings based on ISO3046, BS5514, DIN 6271,  $\pm 5\%$  tolerance. Standard reference conditions: air inlet temperature 27 °C, altitude 100m asl, fuel weight 0.85kg/l, fuel consumption @75% prime load. Prime rating: Continuous running at variable load. No limit to the annual hours of operations. 10% overload capability for 1 hour in any 12 hours. Standby rating: Emergency power at variable load in the event of utility power failure. No overload is permitted.

\* Deration may be necessary at certain voltages.

Due to continually improved products, we reserve the right to make changes in model, technical specs, colour, etc without prior notice.